

# PlumbQwik

The plumbing Industries  
“first choice” in flexible couplings

- Quick and easy to install for a leak proof seal
- Ideal for emergency repairs
- No special tools required
- Ideal for use in confined spaces
- Flexible material for easy jointing of misaligned pipes

**PlumbQwik** The industry's most complete line of fully approved flexible couplings allows any two pipes - regardless of size or material - to be connected quickly and easily.

**PlumbQwik** Flexible Couplings are widely recognised throughout the industry for highest quality combined with over three decades of proven experience.

**PlumbQwik** Flexible Couplings are air, water and smoke tested in the world's most demanding conditions and applications. Fernco has developed an enviable reputation of providing a reliable, consistent and superior performance that enables the plumber and contractor to install the Couplings with assurance and confidence.

All Fernco clamps, including the band screw and housing, are made from series 316 stainless steel thereby meeting the requirements of AS/NZ 4327:1995 'Metal banded flexible couplings for low pressure applications'. They are corrosion resistant and rust proof. Additional band slots have been added for greater flexibility and the bands are specifically designed for greater sealing efficiency. Fernco couplings flex with earth movement, maintaining the Integrity of the seal.

No special tools are needed as the range can be installed easily with screw driver or 5/16" (7.93mm) nut driver or socket (to 50inch/lbs. torque.)

Fernco Australia Pty Ltd hold an extensive stock of all coupling types and sizes which are available for quick distribution to the customer, thereby ensuring a fast, reliable and efficient service. For special applications, our custom design service can supply couplings to individual customer requirements.



## About Fernco

**Fernco (Australia) Pty Ltd** is part of the Fernco group of companies, a global leader in high performance flexible couplings. The company provides a range of PlumbQwik and Flex-Seal branded products to the Australian and New Zealand plumbing and drainage market.

Our world leading range of fully approved flexible couplings are suitable for all sewerage, drainage, plumbing and vent systems.

Manufactured from high performance PVC the Fernco brand of couplings has been extensively tested and approved for low pressure applications throughout the world. The range can be applied to all types of in house and sewer systems produced from any pipe material including plastic, clay, concrete, cast iron, steel and copper.

Our PlumbQwik product range. Includes plumbing and speciality couplings, tees, elbows, shower drain connectors and manhole adaptors. The Flex-Seal product range includes a range of rubber based flexible couplings for low and non pressure applications.



# PlumbQwik

“The plumbers first choice”



Your Local Stockist



## Fernco Australia Pty Ltd

16 Tepko Rd, Terrey Hills, NSW 2084  
Ph: 02 9450 0766 Fax: 02 9450 0377  
www.fernco.com.au  
sales@fernco.com.au



# Flexible coupling sizing chart

Contact us 16 Tepko Rd, Terrey Hills, NSW 2084 | Ph: 02 9450 0766 | Fax: 02 9450 0377 | www.fernco.com.au | sales@fernco.com.au

	Code	Actual Size	Nominal Size
	NEW GREY Couplings suitable for joining PVC to PVC or combinations of PVC, Cast Iron, Copper and Gal		
	1056-50M	55mm X 55mm	50mm PVC
	1056-90M	91mm X 91mm	90mm PVC
	1056-100M	112mm X 112mm	100mm PVC
	1056-150M	162mm X 162mm	150mm PVC
	NEW GREY Couplings suitable for joining Earthenware to PVC		
	1006-100M	142mm X 111mm	100mm EW - 100mm PVC
	1006-150M	198mm X 162mm	150mm EW - 150mm PVC
	Suitable for internal use as drainage pipe connectors for joining PVC to PVC or PVC to Copper/Brass		
	TC-150	38mm X 38mm	32mm PVC - 32mm PVC / 40mm Cu
	DTC-150	48mm X 38mm	40mm PVC - 32mm PVC / 40mm Cu
	DTC-215	58mm X 38mm	50mm PVC - 32mm PVC / 40mm Cu
	Suitable for joining PVC to PVC or combinations of PVC, Cast Iron, Copper and Gal		
	1056-125	40mm X 40mm	32mm PVC
	1056-150	48mm X 48mm	40mm PVC
	1060-150	57mm X 57mm	50mm PVC
	1056-22	60mm X 60mm	50mm PVC
	1060-22	70mm X 70mm	65mm PVC
	1056-33	89mm X 89mm	80mm PVC
	1060-33	100mm X 100mm	90mm PVC socket
	1056-44	112mm X 112mm	100mm PVC
	1056-66	162mm X 162mm	150mm PVC
	1004-88	260mm X 260mm	225mm PVC
	1004-1010	323mm X 323mm	300mm PVC
	1056-1515	391mm X 391mm	375mm PVC

	Code	Actual Size	Nominal Size
	NEW GREY Double band couplings for PVC or combinations of PVC, Cast Iron, Copper or Gal		
	1056-50MDB	55mm X 55mm	50mm PVC
	1056-90MDB	91mm X 91mm	90mm PVC
	1056-100MDB	112mm X 112mm	100mm PVC
	1056-150MDB	162mm X 162mm	150mm PVC
	NEW GREY Double band couplings for joining Earthenware to PVC		
	1006-100MDB	142mm X 111mm	100mm EW - 100mm PVC
	1006-150MDB	198mm X 162mm	150mm EW - 150mm PVC
	Suitable for joining / reducing PVC to PVC Pipe of varying sizes		
	1056-215	60mm x 48mm	50mm PVC - 40mm PVC
	1056-32	85mm x 60mm	80mm PVC - 50mm PVC
	1056-42	111mm X 60mm	100mm PVC - 50mm PVC
	1056-43	111mm X 85mm	100mm PVC - 80mm PVC
	1056-64	162mm X 111mm	150mm PVC - 100mm PVC
	1006-1212	416mm X 318mm	375mm PVC - 300mm PVC
	Suitable for joining Earthenware to PVC or Earthenware to Cast Iron, Copper, Gal		
	1006-43	142mm X 85mm	100mm EW - 80mm PVC
	1006-44	142mm X 111mm	100mm EW - 100mm PVC
	1006-64	198mm X 111mm	150mm EW - 100mm PVC
	1006-66	198mm X 162mm	150mm EW - 150mm PVC
	1004-86	260mm X 198mm	225mm PVC - 150mm EW / Conc
	1051-1010	282mm X 269mm	225mm EW - 225mm PVC
	1002-1212	365mm X 320mm	300mm EW - 300mm PVC
	1002-1515	453mm X 391mm	375mm EW - 375mm PVC
		Suitable for joining Earthenware to Earthenware	
1004-44		142mm X 142mm	100mm EW
1004-66		193mm X 193mm	150mm EW
1055-1010		282mm X 282mm	225mm EW
1001-1212		365mm X 365mm	300mm EW
1001-1515		453mm X 453mm	375mm EW

	Code	Actual Size	Nominal Size
	Suitable for joining AC, FRC or Cast Iron to PVC, Cast Iron, Copper and Gal		
	1051-44	120mm X 111mm	100mm AC, CI or FRC class1 - 100mm PVC
	1051-64	177mm X 111mm	100mm AC or CI - 150mm PVC
	1051-66	177mm X 162mm	150mm AC or CI - 150mm PVC
	1002-66	187mm X 162mm	150mm FRC class1 - 150mm PVC
	1006-1010	320mm X 269mm	225mm AC, FRC Class 1 - 300mm PVC
	Suitable for joining AC to AC and FRC to FRC		
	1055-44	120mm X 120mm	100mm AC
	1001-66	191mm X 191mm	150mm FRC class1
	1056-1010	269mm X 269mm	225mm FRC class1
	Suitable for joining Naylor EW - Naylor EW or PVC		
	1001-66	191mm X 191mm	150mm Naylor EW
	1002-66	187mm X 162mm	150mm Naylor EW - 150mm PVC
	Adjustable Boss Connector 100mm & 150mm X 45deg or 90deg adjust to suit 150, 225, 300, 375mm Pipe		
	TSW-4	100mm inlet	Adjustable 300-225-150 X 100 X 45D
	TSW-6	150mm inlet	Adjustable 375-300-225 X 150 X 45D
	TST-4	100mm inlet	Adjustable 300-225-150 X 100 X 90D
	TST-6	150mm inlet	Adjustable 375-300-225 X 150 X 90D
	TSPK-46	N/A	100mm & 150mm Boss Connector
	Teas and Elbows suitable for 50mm & 100mm PVC or Gal, Cast Iron, Copper. Retrofit compatible.		
	QL-200	57mm	Elbow 50mm X 90deg PVC
	QL-400	112mm	Elbow 100mm X 90deg PVC
	QT-200	57mm	Junction 50mm X 90deg PVC
	QT-400	112mm	Junction 100mm X 90deg PVC

	Code	Actual Size	Nominal Size
	Qwikcap re-usable testing caps for sealing lines, air, smoke or water testing		
	QC-101	48mm	40mm PVC-Cu-Gal-CI
	QC-102	60mm	50mm PVC-Cu-Gal-CI
	QC-103	85mm	80mm PVC-Cu-Gal-CI
	QC-104	112mm	100mm PVC-Cu-Gal-CI
	QC-105	142mm	100mm EW
	QC-106	162mm	150mm PVC-Cu-Gal-CI
	Shear Rings in 316 Stainless Steel add strength and rigidity to standard couplings		
	SR-19	111mm X 50mm	100mm PVC X 50mm wide
	SR-27	162mm X 100mm	150mm PVC X 100mm wide
	SR-28	198mm X 100mm	150mm EW X 100mm wide
	Expansion Joints for vertical installations suit 50mm & 100mm PVC or Gal, Cast Iron, Copper		
	XJ-2	57mm	50mm PVC
	XJ-4	112mm	100mm PVC
	Conduit and Condensation drain connectors - NOT for pressure applications		
	DWC-100	20mm	15mm PVC conduit 20mm Cu
	1056-075	25mm	20mm PVC conduit 25mm Cu
	1056-100	32mm	25mm PVC conduit 32mm Cu
	Washing machine Hose Grip Connector. Clamps to 50mm DWV secures washing machine drain hose		
	HG-1	57mm	50mm PVC
	Torque Wrench to suit hex head hose clamp screws		
	TW-100	5/6"	N/A
	Fernco Pipe Doctor No Dig Pipe Repair System		
	PD-100	70-103mm ID	Repair Kit
	PD-150	104-154mm ID	Repair Kit
	PDAPR15b	1.5m length	Air Push Rod
	PDFA1	N/A	Flexible Adaptor
	PDSP10/15/15	1.5m length	Packer
	Pow-R Wrap Strong, permanent, water activated pipe repair kit		
	FPW 248CS	50mmW x 1200L	Repairs up to 25mm
	FPW 3132CS	75mm W x 3300L	Repairs 32mm to 75mm
	FPW 4242CS	100mmW x 6300L	Repair 80mm to 150mm